



# inoCOMB Picco Power

The light and compact 230 V mixing pump for mineral and paste-like materials

## Benefits at a glance

- **Power output:** 3.0 kW and 230 V, making a delivery range of 30 m and a delivery height of 20 m achievable
- Continuously variable delivery rate
- Stainless steel material hopper
- Simple cleaning thanks to PU mixing zone
- Powerful compressor – can also be used for processing decorative finish coatings
- The total weight without the compressor is only 65 kg! This therefore makes transport easy!



The **inoCOMB Picco Power** is a trendsetter among compact 230 V mixing pumps. With its power output, a delivery range of 30 m and delivery height of 20 m are easily achievable. As a result, the **Picco Power** – even without high-voltage current – is very versatile on any construction site. Parts that come into contact with materials, such as the hopper, mixing shaft, pump flange and protective screen, are made of high-quality stainless steel. The simple operation and easy-to-clean PU mixing zone ensure smooth operation right from the start.

## Areas of application

Internal and external mineral plasters, renovating plasters, paste-like fillers, reinforcing plasters and final coats, floor leveling compounds, ETICS bonding / basecoat mortars and much more (see table on page 6)

## Technical data

Operating pressure max.	30 bar
Operating voltage	230 V / 16 A / 50 Hz
Motor rating	3.0 kW
Delivery rate	frequency-controlled approx. 0 - 18 l/min (paste-like) approx. 8 - 30 l/min (mineral)
delivery range	Up to 30 m*
Delivery height	Up to 20 m*
Material hopper	approx. 55 l
Fill level	1,000 mm
Dimensions (L x W x H)	approx. 1,560 x 640 x 1,090 mm
Weight	approx. 65 kg excluding compressor approx. 97 kg with compressor

\* Depending on the material consistency

## Basic module Item no. 10041148

### Scope of delivery inoCOMB Picco Power:

- Frame
- 4 running wheels
- Material hopper made from stainless steel
- PU mixing zone
- Gear motor
- Rotor/stator  
D 7-2.5 "Mono Plus"
- Switching cabinet
- 15 m, 230 V Schuko / CEE connecting cable
- Mortar pressure gauge
- Mixing coil
- Water fitting
- Tool set
- Assembly spray lubricant
- Operating instructions



## Ready-to-spray set Item no. 10041149

### Scope of delivery inoCOMB Picco Power Set:

As with the basic module  
(item no. 10041148)

#### Plus:

- C 330 PP compressor
- 10 m mortar hose with a diameter of 25 mm
- 15 m air hose with a diameter of 1/2"
- Straight finishing coat device incl. nozzle with a diameter of 12 mm, 14 mm